

Amendments to the Claims:

This Listing of Claims will replace all prior versions, and listings, of claims in the Application:

Listing of Claims:

1-12. (Cancelled).

13. (New): A vehicle seat having an upholstered component and a backrest component (1), the backrest component (1) being provided so that it can be rotatably moved about a first axis (A), said first axis (A) being provided parallel to a transversal direction that runs transversally to the primary sitting direction (7), wherein the seat upholstered component (2) is provided to be rotatably moved relative to the seat lower component (8) about a second axis (B) provided parallel to the transversal direction (9) from an upholstered component use position into an upholstered component loading position and vice versa, and the backrest component (1) being provided so that it can be rotatably moved relative to the seat lower component (8) about the first axis (A) from a backrest use position into a backrest loading position and vice versa only when the seat upholstered component (2) has been moved substantially into the upholstered component loading position.

14. (New): The vehicle seat (10) of claim 13 wherein the seat upholstered component (2) has a use side (22) and a non-use side (21), the non-use side (21) of the seat upholstered component (2) being disposed facing the backrest component (1) when the seat upholstered component (2) is in the upholstered component loading position.

15. (New): The vehicle seat (10) of claim 14 wherein the backrest component (1) in its backrest loading position is disposed substantially horizontally.

16. (New): The vehicle seat (10) of claim 15 wherein the seat lower component (8) has a first lower component (5) and a second lower component (6), the first lower component (5) together with the seat upholstered component (2) and the backrest component (1) being provided so that it can be rotatably moved about a third axis (C), different from the

second axis (B) and provided parallel to the transversal direction (9), from a use position into a folded-over position and vice versa.

17. (New): The vehicle seat (10) of claim 16 wherein the backrest component (1) is provided so that it can be rotatably moved about the first axis (A) from the backrest use position into a backrest folded-over position, different from the backrest loading position, parallel to the transversal direction (9) and vice versa when the seat upholstered component (2) is situated in the upholstered use position relative to the first lower component (5).

18. (New): The vehicle seat (10) of claim 17 wherein the backrest component folded-over position relative to the first lower component (5) is passed through when the backrest component (1) is moved from the backrest component use position into the backrest component loading position.

19. (New): The vehicle seat (10) of claim 18 wherein the backrest component (1) situated in a backrest component folded-over position relative to the second lower component (6) and also the upholstered component (2) situated in an upholstered component folded-over position relative to the second lower component (6) and the first lower component (5) situated in the folded-over position relative to the second lower component (6) are disposed so that they are substantially vertically adjustable in each case.